



MIRAFI H₂Ri

MIRAFI® H₂Ri is a revolutionary geosynthetic created from super high-tenacity polypropylene filaments and patented moisture management filaments formed into an innovative weave to provide superior reinforcement strength and soil interaction integrated with high soil retention and moisture management capabilities.

Geosynthetic directionally draws water via capillary action.

TenCate Geosynthetics Americas (A Solmax Company) is accredited by Geosynthetic Accreditation Institute – Laboratory Accreditation Program ([GAI-LAP](#)).

MIRAFI® H₂Ri meets Build America, Buy America Act, Pub. L. No. 117-58, div. G §§ 70901-52.

MECHANICAL PROPERTIES	TEST METHOD	UNIT	MINIMUM AVERAGE ROLL VALUE	
			MD	CD
Wide Width Tensile Strength	ASTM D4595	lbs/ft (kN/m)	5280 (77.0)	5280 (77.0)
Wide Width Tensile Strength @ 2% strain	ASTM D4595	lbs/ft (kN/m)	480 (7.0)	1080 (15.8)
MAXIMUM OPENING SIZE				
Apparent Opening Size (AOS)	ASTM D4751	U.S. Sieve (mm)	40 (0.425)	
MINIMUM ROLL VALUE				
Permittivity	ASTM D4491	sec ⁻¹	0.4	
Flow Rate	ASTM D4491	gal/min/ft ² (l/min/m ²)	30 (1222)	
TYPICAL				
Pore Size (050)	ASTM D6767	microns	180	
Pore Size (060)	ASTM D6767	microns	234	
Pore Size (095)	ASTM D6767	microns	391	
MINIMUM TEST VALUE				
Wet Front Movement ¹ (24 minutes)	ASTM C1559 ²	inches	6.0 Vertical direction	
Wet Front Movement ¹ (983 minutes) Zero Gradient	ASTM C1559 ²	inches	73.3 Horizontal direction	
PHYSICAL PROPERTIES		UNIT	TYPICAL ROLL VALUE	
Roll Dimensions (width x length)		ft (m)	15 x 300 (4.59 x 91.44)	
Roll Area		yd ² (m ²)	500 (418)	

¹ 'STP': Standard Temperature and Pressure

² Modified

365 South Holland Drive Pendergrass, GA 30567

Tel +1 706 693 2226 www.tencategeo.us



Solmax is not a design or engineering professional and has not performed any such design services to determine if Solmax's goods comply with any project plans or specifications, or with the application or use of Solmax's goods to any particular system, project, purpose, installation, or specification.
FGS000731 ETQR17 U.S. Patent 7,874,767 and 8,070,395

